

Revision Number: 001.3

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

Product type/use: Acrylic Restriction of Use: None in Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

LePage No More Nails Paneling and Moulding Construction Adhesive Acrylic Adhesive None identified IDH number:

2048232

Region:United StatesContact information:Telephone: +1 (860) 571-5100MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

 EMERGENCY OVERVIEW

 WARNING:
 CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2A

PICTOGRAM(S)	

Precautionary Statements

Prevention: Response: Storage: Disposal: Wash affected area thoroughly after handling. Wear eye and face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Not prescribed Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Limestone	1317-65-3	30 - 40	
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5	
Distillates (petroleum), hydrotreated light	64742-47-8	1 - 5	
Quartz (SiO2), <1% respirable	14808-60-7	0.1 - 1	

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4.	FIRST AID MEASURES	
Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.	
Skin contact:	Wash with soap and water. If symptoms develop and persist, get medical attention.	
Eye contact:	Flush eyes with plenty of water for at least 5 minutes. If irritation persists seek medical attention.	
Ingestion:	Do not induce vomiting. Seek medical advice.	
Symptoms:	See Section 11.	
5. FIRE FIGHTING MEASURES		
Extinguishing media:	carbon dioxide, foam, powder, water spray jet, fine water spray	
Special firefighting procedures:	Not available.	
Unusual fire or explosion hazards:	None known.	

• • • • • •

Hazardous combustion products:

Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: None known

Scrape up as much material as possible. Clean residue with soap and water.

7. HANDLING AND STORAGE

Handling:

Clean-up methods:

Avoid contact with eyes. Avoid prolonged or repeated skin contact with this material. Do not taste or swallow. Keep out of the reach of children.

Storage:

Protect from freezing. Store in a cool, dry area.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	20 MPPCF TWA 0.8 mg/m3 TWA 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Distillates (petroleum), hydrotreated light	(SKIN) (as total hydrocarbon vapor) Non-aerosol. 200 mg/m3 TWA (as total hydrocarbon vapor) Non-aerosol. (SKIN) (as total hydrocarbon vapor) Non-aerosol.	None	None	None
Quartz (SiO2), <1% respirable	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None

Engineering controls: Respiratory protection: Not normally needed.

No personal respiratory protective equipment normally required.

No special measures required if used properly.

Eye/face protection: Skin protection:

No special measures required if used properly.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point:

IDH number: 2048232

Solid White Acrylic Not available. 7 - 9 Not available. 100 °C (212°F) Not available. 1.03 - 1.07 (Water = 1) 0.62 (Air = 1) Not classified as a flammable solid per DOT Classification Guidelines Part 173 Appendix H 7/10/2002. Product name: LePage No More Nails Paneling and Moulding Construction Adhesive Page 3 of 6 Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Flammability: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content:

Decomposition temperature:

Viscosity:

Not available. Not available. Not available. Not applicable 1 (Water = 1) emulsifiable Not available. 0.1 %; 27 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method) 2,000,000 mPa.s Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.	
Hazardous reactions:	Will not occur.	
Hazardous decomposition products:	None known	
Incompatible materials:	Strong acids and oxidizing agents.	
Reactivity:	Not available.	
Conditions to avoid:	None known.	
11. TOXICOLOGICAL INFORMATION		

Relevant routes of exposure: Eyes, Skin

Potential Health Effects/Symptoms

Inhalation:	Not a relevant route of exposure. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.
Skin contact:	Prolonged and/or repeated skin contact with this product may cause irritation.
Eye contact:	May cause irritation.
Ingestion:	Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Limestone	None	Nuisance dust
Silica, amorphous, fumed, crystal-free	None	Nuisance dust
Distillates (petroleum), hydrotreated light	Inhalation LC50 (Rat, 4 h) = > 4.6 mg/l Inhalation LC50 (Rat, 4 h) = > 4.3 mg/l Inhalation LC50 (Rat, 4 h) = > 4.5 mg/l Inhalation LC50 (Rat, 4 h) = > 5.68 mg/l Inhalation LC50 (Rat, 4 h) = > 5.3 mg/l Inhalation LC50 (Rat, 4 h) = > 5.28 mg/l Inhalation LC50 (Rat, 4 h) = > 5.2 mg/l Inhalation LC50 (Rat, 4 h) = > 5.2 mg/l	Irritant, Lung
Quartz (SiO2), <1% respirable	None	Immune system, Lung, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No
Distillates (petroleum), hydrotreated light	No	No	No
Quartz (SiO2), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

Product name: LePage No More Nails Paneling and Moulding Construction Adhesive Page 4 of 6

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Hazard class or division: Identification number: Packing group: Not regulated None None None

International Air Transportation (ICAO/IATA)

Proper shipping name: Hazard class or division: Identification number: Packing group: Not regulated None None None

Water Transportation (IMO/IMDG)

Proper shipping name: Hazard class or division: Identification number: Packing group: Not regulated None None None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.	
TSCA 12 (b) Export Notification:	None above reporting de minimis	
CERCLA/SARA Section 302 EHS:	None above reporting de minimis. Ammonia, aqueous solution (CAS# 1336-21-6). Acrylamide (CAS# 79-06-1). Ethylene oxide (CAS# 75-21-8).	
CERCLA/SARA Section 311/312:	None	
CERCLA/SARA Section 313:	None above reporting de minimis.	
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.	
Canada Regulatory Information		
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic	

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 06/05/2023

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.