



Revision Number: 006.0

Issue date: 08/06/2021

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product name:</b>	<b>LePage No More Drafts Removable Sealant</b>	<b>IDH number:</b>	1732921
<b>Product type/use:</b>	Sealant	<b>Region:</b>	Canada
<b>Restriction of Use:</b>	None identified	<b>Contact information:</b>	Telephone: +1 (905) 814-6511 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com
<b>Company address:</b>	Henkel Canada Corporation Meadowpine Boulevard 2515 Mississauga, Ontario L5N 6C3		

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

**WARNING:** FLAMMABLE LIQUID AND VAPOR.  
CAUSES SKIN IRRITATION.  
CAUSES SERIOUS EYE IRRITATION.  
MAY CAUSE RESPIRATORY IRRITATION.  
MAY CAUSE DROWSINESS OR DIZZINESS.  
SUSPECTED OF CAUSING CANCER.  
MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	3
SKIN IRRITATION	2
EYE IRRITATION	2A
CARCINOGENICITY	2
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2

**PICTOGRAM(S)**



**Precautionary Statements**

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, clothing, eye and face protection.

**Response:** If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes.

IDH number: 1732921

Product name: LePage No More Drafts Removable Sealant

Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Stoddard solvent, <0.1% Benzene	8052-41-3	20 - 30
Xylenes	1330-20-7	10 - 20
Butene, homopolymer	9003-29-6	5 - 10
Ethylbenzene	100-41-4	5 - 10
1,2,4-Trimethylbenzene	95-63-6	1 - 5
Naphthalene	91-20-3	0.1 - 1

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

**Inhalation:** If inhaled, immediately remove the affected person to fresh air. If symptoms develop and persist, get medical attention.

**Skin contact:** Wash affected area immediately with soap and water. If symptoms develop and persist, get medical attention.

**Eye contact:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

**Ingestion:** Do not induce vomiting: contains petroleum distillates and/or aromatic solvents. Seek medical advice.

**Symptoms:** See Section 11.

### 5. FIRE FIGHTING MEASURES

**Extinguishing media:** Foam, dry chemical or carbon dioxide.

**Special firefighting procedures:** Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Water stream directed into fire may cause frothing with subsequent spread of flame.

**Unusual fire or explosion hazards:** Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. Decomposition and combustion products may be toxic. Empty containers retain product residue, so obey hazard warnings and handle empty containers as if they were full. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition.

**Hazardous combustion products:**

Acrid smoke and fumes. Oxides of carbon.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:**

Remove all sources of ignition. Ventilate area. Wear appropriate protective equipment and clothing during clean-up. Dike the spilled material, where this is possible. Prevent further leakage or spillage if safe to do so. Flush area with water to remove trace residue. Do not allow product to enter sewer or waterways.

**Clean-up methods:**

Absorb spill with inert material. Shovel material into appropriate container for disposal. Clean residue with soap and water. Allow to solidify. Dispose of according to Federal, State and local governmental regulations.

## 7. HANDLING AND STORAGE

**Handling:**

Avoid all ignition sources in storing and handling this material. Keep cool in accordance with label instructions. Wear protective equipment when handling. Avoid breathing vapors or mists of this product. Avoid contact with eyes, skin and clothing. Keep out of the reach of children. Use only with adequate ventilation. Containers should be grounded and bonded to the receiving container.

**Storage:**

Keep away from heat, spark and flame.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Stoddard solvent, <0.1% Benzene	100 ppm TWA	500 ppm (2,900 mg/m <sup>3</sup> ) PEL	None	None
Xylenes	100 ppm TWA 150 ppm STEL	100 ppm (435 mg/m <sup>3</sup> ) PEL	None	None
Butene, homopolymer	None	None	None	None
Ethylbenzene	20 ppm TWA	100 ppm (435 mg/m <sup>3</sup> ) PEL	None	None
1,2,4-Trimethylbenzene	25 ppm TWA	None	None	None
Naphthalene	10 ppm TWA (SKIN)	10 ppm (50 mg/m <sup>3</sup> ) PEL	None	None

**Engineering controls:**

Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

**Respiratory protection:**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH.

**Eye/face protection:**

Safety goggles or safety glasses with side shields.

**Skin protection:**

Chemical resistant, impermeable gloves. Recommended gloves include rubber and neoprene.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid
<b>Color:</b>	Clear
<b>Odor:</b>	mild
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not applicable
<b>Vapor pressure:</b>	22.7 mm hg (20 °C (68°F))
<b>Boiling point/range:</b>	Not available.
<b>Melting point/ range:</b>	Not available.
<b>Specific gravity:</b>	0.86
<b>Vapor density:</b>	Heavier than air, (Air = 1)
<b>Flash point:</b>	25 °C (77°F) no method
<b>Flammable/Explosive limits - lower:</b>	0.9 % (value for solvent)
<b>Flammable/Explosive limits - upper:</b>	7 % (value for solvent)
<b>Autoignition temperature:</b>	Not available.
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	Slower than butyl acetate.
<b>Solubility in water:</b>	Insoluble
<b>Partition coefficient (n-octanol/water):</b>	Not applicable
<b>VOC content:</b>	56 %; 486 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method)
<b>Viscosity:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of storage and use.
<b>Hazardous reactions:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	Acrid smoke and fumes. Oxides of carbon.
<b>Incompatible materials:</b>	Reaction with strong bases Reaction with strong oxidants. Strong Lewis acids. Strong mineral acids.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Keep away from open flames, hot surfaces and sources of ignition.

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes, Ingestion

**Potential Health Effects/Symptoms**

**Inhalation:** May be harmful if inhaled. May cause irritation to nose and throat. May cause central nervous system effects, such as headache, nausea, vomiting, abdominal pain, dizziness, confusion, and breathing difficulties. May cause narcosis at high concentrations. Repeated inhalation of high vapor/mist concentrations may cause pulmonary, liver and kidney injury.

**Skin contact:** Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

**Eye contact:** Contact with uncured product may irritate the eyes.

**Ingestion:** May be harmful or fatal if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Stoddard solvent, <0.1% Benzene	None	Central nervous system, Irritant
Xylenes	Oral LD50 (Rat) = 6,670 mg/kg Oral LD50 (Rat) = 3,523 - 8,600 mg/kg Oral LD50 (Rat) = 4,300 mg/kg Dermal LD50 (Rabbit) = > 43 g/kg Inhalation LC50 (Rat, 4 h) = 6580 ppm Inhalation LC50 (Rat, 4 h) = 6247 ppm Inhalation LC50 (Rat, 4 h) = 5922 ppm Inhalation LC50 (Rat, 4 h) = 6700 ppm Inhalation LC50 (Rat, 4 h) = 6350 ppm	Cardiac, Central nervous system, Irritant, Kidney, Liver
Butene, homopolymer	Inhalation LC50 (Rat, 4 h) = > 4185 ppm Inhalation LC50 (Rat, 4 h) = > 19,171 mg/m3	No Data
Ethylbenzene	Oral LD50 (Rat) = 5.46 g/kg Oral LD50 (Rat) = 3,500 mg/kg Dermal LD50 (Rabbit) = 17,800 mg/kg Inhalation LC50 (Rat, 4 h) = 4000 ppm	Irritant, Central nervous system
1,2,4-Trimethylbenzene	Oral LD50 (Rat) = 6.0 g/kg Dermal LD50 (Rabbit) = > 3,160 mg/kg Inhalation LC50 (Rat, 4 h) = 10,200 mg/m3 Inhalation LC50 (Rat, 4 h) = 18,000 mg/m3	Central nervous system, Irritant, Respiratory
Naphthalene	Oral LD50 (Rat) = 490 mg/kg Oral LD50 (Rat) = 2.6 g/kg Oral LD50 (Rat) = 2,200 mg/kg Oral LD50 (Rat) = 2,400 mg/kg Dermal LD50 (Rat) = > 20 g/kg Dermal LD50 (Rabbit) = > 2.0 g/kg Inhalation LC50 (Rat, 4 h) = > 0.4 mg/l Inhalation LC50 (Rat, 4 h) = > 78 ppm	Blood, Central nervous system, Eyes, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Stoddard solvent, <0.1% Benzene	No	No	No
Xylenes	No	No	No
Butene, homopolymer	No	No	No
Ethylbenzene	No	Group 2B	No
1,2,4-Trimethylbenzene	No	No	No
Naphthalene	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No

**12. ECOLOGICAL INFORMATION**

**Ecological information:** Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### Canada Transportation of Dangerous Goods - Ground

**Proper shipping name:** ADHESIVES  
**Hazard class or division:** 3  
**Identification number:** UN 1133  
**Packing group:** III

#### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Adhesives  
**Hazard class or division:** 3  
**Identification number:** UN 1133  
**Packing group:** III

#### Water Transportation (IMO/IMDG)

**Proper shipping name:** ADHESIVES  
**Hazard class or division:** 3  
**Identification number:** UN 1133  
**Packing group:** III

### 15. REGULATORY INFORMATION

#### Canada Regulatory Information

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

#### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

### 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** This Safety Data Sheet contains changes from the previous version in Section(s): 2, 3, 8, 11

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 08/06/2021

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.