



Revision Number: 004.0

Issue date: 11/20/2019

1. PRODUCT AND COMPANY IDENTIFICATION

| | | | |
|-------------------------------|--|--|---------------|
| Product name: | LOCTITE EDAG 423SS 200G E&C | IDH number: | 2030387 |
| Product type/use: | Coating | Region: | United States |
| Restriction of Use: | None identified | Contact information: | |
| Company address: | | Telephone: +1 (860) 571-5100 | |
| Henkel Corporation | | MEDICAL EMERGENCY Phone: Poison Control Center | |
| One Henkel Way | | 1-877-671-4608 (toll free) or 1-303-592-1711 | |
| Rocky Hill, Connecticut 06067 | | TRANSPORT EMERGENCY Phone: CHEMTREC | |
| | | 1-800-424-9300 (toll free) or 1-703-527-3887 | |
| | | Internet: www.henkelna.com | |

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: COMBUSTIBLE LIQUID.

| HAZARD CLASS | HAZARD CATEGORY |
|------------------|-----------------|
| FLAMMABLE LIQUID | 4 |

PICTOGRAM(S)

None

Precautionary Statements

| | |
|--------------------|---|
| Prevention: | Keep away from heat, sparks, open flames, hot surfaces - no smoking. Wear protective gloves, eye protection, and face protection. |
| Response: | In case of fire: Use foam, dry chemical or carbon dioxide to extinguish. |
| Storage: | Store in a well-ventilated place. Keep cool. |
| Disposal: | Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations. |

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* |
|--|------------|-------------|
| Butoxyethyl acetate | 112-07-2 | 60 - 80 |
| Graphite | 7782-42-5 | 10 - 30 |
| Carbon black | 1333-86-4 | 5 - 10 |
| Quartz (SiO ₂), <1% respirable | 14808-60-7 | 0.1 - 1 |

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

| | |
|----------------------|--|
| Inhalation: | Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. |
| Skin contact: | Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse. |
| Eye contact: | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention. |
| Ingestion: | DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention. |
| Symptoms: | See Section 11. |

5. FIRE FIGHTING MEASURES

| | |
|---|--|
| Extinguishing media: | Water spray (fog), foam, dry chemical or carbon dioxide. |
| Special firefighting procedures: | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray. |
| Unusual fire or explosion hazards: | Closed containers may rupture (due to build up of pressure) when exposed to extreme heat. |
| Hazardous combustion products: | Oxides of carbon. Toxic fumes. Irritating vapors. |

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

| | |
|-----------------------------------|---|
| Environmental precautions: | Do not allow product to enter sewer or waterways. |
| Clean-up methods: | Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal. |

7. HANDLING AND STORAGE

| | |
|------------------|--|
| Handling: | Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. |
| Storage: | For safe storage, store between -20 °C (-4°F) and 50 °C (122°F) Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Keep away from heat, spark and flame. Protect from direct sunlight. |

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|--|---|---|-----------|-------|
| Butoxyethyl acetate | 20 ppm TWA | None | None | None |
| Graphite | 2 mg/m3 TWA Respirable fraction. | 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. | None | None |
| Carbon black | 3 mg/m3 TWA Inhalable fraction. | 3.5 mg/m3 PEL | None | None |
| Quartz (SiO ₂), <1% respirable | 0.025 mg/m3 TWA Respirable fraction. | 0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. | None | None |

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|--------------------------------|
| Physical state: | Liquid |
| Color: | Black |
| Odor: | Sweet |
| Odor threshold: | Not available. |
| pH: | Not available. |
| Vapor pressure: | Not available. |
| Boiling point/range: | Not available. |
| Melting point/ range: | Not available. |
| Specific gravity: | 1.13 |
| Vapor density: | Not available. |
| Flash point: | 73.8 °C (164.84 °F) Closed cup |
| Flammable/Explosive limits - lower: | Not available. |
| Flammable/Explosive limits - upper: | Not available. |
| Autoignition temperature: | Not available. |
| Flammability: | Combustible Liquid |
| Evaporation rate: | Not available. |
| Solubility in water: | Not available. |
| Partition coefficient (n-octanol/water): | Not available. |
| VOC content: | 730 g/l |
| Viscosity: | Not available. |
| Decomposition temperature: | Not available. |

10. STABILITY AND REACTIVITY

| | |
|--|---|
| Stability: | Stable under normal conditions of storage and use. |
| Hazardous reactions: | None under normal processing. |
| Hazardous decomposition products: | Oxides of carbon. Toxic fumes. Irritating vapors. |
| Incompatible materials: | Strong oxidizing agents. Strong acids and strong bases. |
| Reactivity: | Not available. |
| Conditions to avoid: | Keep away from heat, ignition sources and incompatible materials. Protect from direct sunlight. |

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

| | |
|----------------------|--|
| Inhalation: | May cause respiratory tract irritation. May cause central nervous system effects with nausea, dizziness and headache. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release. |
| Skin contact: | May cause skin irritation. |
| Eye contact: | May cause eye irritation. Redness. Tearing. |
| Ingestion: | May cause gastrointestinal tract irritation if swallowed. |

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects |
|--|--|---|
| Butoxyethyl acetate | Oral LD50 (Rat) = 2,400 mg/kg Oral LD50 (Rat) = 3,000 mg/kg Dermal LD50 (Rabbit) = 1,500 mg/kg | Behavioral, Blood, Bone Marrow, Central nervous system, Irritant, Kidney, Liver, Lung |
| Graphite | Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m ³ Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m ³ | Lung |
| Carbon black | Oral LD50 (Rat) = > 8,000 mg/kg | Respiratory, Some evidence of carcinogenicity |
| Quartz (SiO ₂), <1% respirable | None | Immune system, Lung, Some evidence of carcinogenicity |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--|-------------------------------|-----------------|--|
| Butoxyethyl acetate | No | No | No |
| Graphite | No | No | No |
| Carbon black | No | Group 2B | No |
| Quartz (SiO ₂), <1% respirable | Known To Be Human Carcinogen. | Group 1 | Yes |

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.
Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Combustible liquid, n.o.s. (Ethylene glycol monobutyl ether acetate)
Hazard class or division: Combustible Liquid
Identification number: NA 1993
Packing group: III

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Fire
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Butoxyethyl acetate (CAS# 112-07-2).
California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,3,7,11,15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 11/20/2019

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.