



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 16

LOCTITE EDAG PF 455B 1.0KGX E&C

SDS No. : 325652
V006.0

Revision: 05.09.2019
printing date: 19.04.2021

Replaces version from: 27.08.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE EDAG PF 455B 1.0KGX E&C

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

UV curable dielectric ink

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000

Fax-no.: +44 1442 278071

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Specific target organ toxicity - single exposure	Category 3
H335 May cause respiratory irritation.	
Target organ: respiratory tract irritation	
Chronic hazards to the aquatic environment	Category 2
H411 Toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:**Contains**

2-[(3a,4,5,6,7,7a-Hexahydro-4,7-methano-1H-inden-6-yl)oxy]ethyl acrylate

Signal word:

Warning

Hazard statement:

H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H411 Toxic to aquatic life with long lasting effects.

Supplemental information

Contains Isobornyl acrylate; 1,6-Hexanediol diacrylate. May produce an allergic reaction.

**Precautionary statement:
Prevention**

P261 Avoid breathing vapors.
 P273 Avoid release to the environment.

**Precautionary statement:
Response**

P302+P352 IF ON SKIN: Wash with plenty of soap and water.
 P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Base substances of preparation:**

Pigment
 polymers

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
2-[(3a,4,5,6,7,7a-Hexahydro-4,7-methano-1H-inden-6-yl)oxy]ethyl acrylate 65983-31-5	265-991-6	25- 50 %	Skin Irrit. 2; Dermal H315 Eye Irrit. 2 H319 STOT SE 3; Inhalation H335 Aquatic Chronic 2 H411
2-Hydroxy-2-methylpropiophenone 7473-98-5	231-272-0 01-2119472306-39	1- < 10 %	Aquatic Chronic 3 H412 Acute Tox. 4; Oral H302
Polybutadiene acrylate~		1- < 5 %	Skin Irrit. 2 H315 Eye Irrit. 2 H319
Isobornyl acrylate 5888-33-5	227-561-6 01-2119957862-25	0,1- < 1 %	Skin Irrit. 2 H315 Eye Irrit. 2 H319 STOT SE 3 H335 Skin Sens. 1B H317 Aquatic Acute 1 H400 Aquatic Chronic 1 H410
1,6-Hexanediol diacrylate 13048-33-4	235-921-9 01-2119484737-22	0,01- < 0,1 %	Aquatic Acute 1 H400 Aquatic Chronic 2 H411 Skin Irrit. 2 H315 Eye Irrit. 2 H319 Skin Sens. 1A H317

For full text of the H - statements and other abbreviations see section 16 "Other information".
Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air.

In case of adverse health effects seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

Carbon dioxide, foam, powder

Water spray jet

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

The product may undergo spontaneous polymerization at high temperatures. Polymerization is exothermic and may cause damage to the container and/or release of thermal decomposition products.

Formation of toxic gases is possible during heating or in fires.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures**General information:**

Danger of slipping on spilled product.

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Avoid skin and eye contact.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid skin and eye contact.

Use only in well-ventilated areas.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container.
 Store in a cool, well-ventilated place.
 Refer to Technical Data Sheet

7.3. Specific end use(s)

UV curable dielectric ink

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for
 Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC, RESPIRABLE DUST]		1	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for
 Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC, TOTAL INHALABLE DUST]		10	Time Weighted Average (TWA):		IR_OEL
Talc (Mg ₃ H ₂ (SiO ₃) ₄) 14807-96-6 [TALC, RESPIRABLE DUST]		0,8	Time Weighted Average (TWA):		IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
2-Hydroxy-2-methylpropiophenone 7473-98-5	aqua (freshwater)		0,00195 mg/l				
2-Hydroxy-2-methylpropiophenone 7473-98-5	aqua (marine water)		0,000195 mg/l				
2-Hydroxy-2-methylpropiophenone 7473-98-5	aqua (intermittent releases)		0,0195 mg/l				
2-Hydroxy-2-methylpropiophenone 7473-98-5	sediment (freshwater)				0,00514 mg/kg		
2-Hydroxy-2-methylpropiophenone 7473-98-5	sediment (marine water)				0,000514 mg/kg		
2-Hydroxy-2-methylpropiophenone 7473-98-5	Soil				0,000674 mg/kg		
2-Hydroxy-2-methylpropiophenone 7473-98-5	sewage treatment plant (STP)		45 mg/l				
Isobornyl acrylate 5888-33-5	aqua (freshwater)		0,00092 mg/l				
Isobornyl acrylate 5888-33-5	aqua (marine water)		0,000092 mg/l				
Isobornyl acrylate 5888-33-5	sewage treatment plant (STP)		2 mg/l				
Isobornyl acrylate 5888-33-5	aqua (intermittent releases)		0,00704 mg/l				
Isobornyl acrylate 5888-33-5	sediment (freshwater)				0,145 mg/kg		
Isobornyl acrylate 5888-33-5	sediment (marine water)				0,0145 mg/kg		
Isobornyl acrylate 5888-33-5	Soil				0,0285 mg/kg		
Isobornyl acrylate 5888-33-5	Air						
Isobornyl acrylate 5888-33-5	Predator						
Hexamethylene diacrylate 13048-33-4	aqua (freshwater)		0,0015 mg/l				
Hexamethylene diacrylate 13048-33-4	aqua (marine water)		0,00015 mg/l				
Hexamethylene diacrylate 13048-33-4	Soil				0,00397 mg/kg		
Hexamethylene diacrylate 13048-33-4	sewage treatment plant (STP)		2,7 mg/l				
Hexamethylene diacrylate 13048-33-4	sediment (freshwater)				0,0243 mg/kg		
Hexamethylene diacrylate 13048-33-4	sediment (marine water)				0,00243 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
2-Hydroxy-2-methylpropiophenone 7473-98-5	Workers	inhalation	Acute/short term exposure - systemic effects		3,5 mg/m ³	
2-Hydroxy-2-methylpropiophenone 7473-98-5	Workers	inhalation	Long term exposure - systemic effects		3,5 mg/m ³	
2-Hydroxy-2-methylpropiophenone 7473-98-5	Workers	dermal	Long term exposure - systemic effects		1,25 mg/kg	
Isobornyl acrylate 5888-33-5	Workers	dermal	Long term exposure - systemic effects		1,39 mg/kg	
Isobornyl acrylate 5888-33-5	General population	oral	Long term exposure - systemic effects		0,83 mg/kg	
Isobornyl acrylate 5888-33-5	General population	dermal	Long term exposure - systemic effects		0,83 mg/kg	
Hexamethylene diacrylate 13048-33-4	Workers	dermal	Long term exposure - systemic effects		2,77 mg/kg	
Hexamethylene diacrylate 13048-33-4	Workers	Inhalation	Long term exposure - systemic effects		24,48 mg/m ³	
Hexamethylene diacrylate 13048-33-4	General population	dermal	Long term exposure - systemic effects		1,66 mg/kg	
Hexamethylene diacrylate 13048-33-4	General population	Inhalation	Long term exposure - systemic effects		7,24 mg/m ³	
Hexamethylene diacrylate 13048-33-4	General population	oral	Long term exposure - systemic effects		2,08 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/suction at the workplace.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid
Odor	green characteristic
Odour threshold	No data available / Not applicable
pH	Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	204 °C (399.2 °F)
Flash point	93,3 °C (199.94 °F); None
Evaporation rate	No data available / Not applicable
Flammability	No data available / Not applicable
Explosive limits	No data available / Not applicable
Vapour pressure	0,1 mm hg
Relative vapour density:	No data available / Not applicable
Density (20 °C (68 °F))	1,020 g/cm ³
Bulk density	No data available / Not applicable
Solubility	No data available / Not applicable
Solubility (qualitative) (Solvent: Water)	Insoluble
Partition coefficient: n-octanol/water	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Decomposition temperature	No data available / Not applicable
Viscosity ()	11.500 cp
Viscosity (kinematic)	No data available / Not applicable
Explosive properties	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong bases
Reaction with strong oxidants.
Reducing agents.
Peroxides.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Protect from direct sunlight.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None if used for intended purpose.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
2-[(3a,4,5,6,7,7a-Hexahydro-4,7-methano-1H-inden-6-yl)oxy]ethyl acrylate 65983-31-5	LD50	> 5.000 mg/kg	rat	
2-Hydroxy-2-methylpropiophenone 7473-98-5	LD50	1.694 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Isobornyl acrylate 5888-33-5	LD50	4.350 mg/kg	rat	not specified
1,6-Hexanediol diacrylate 13048-33-4	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
2-[(3a,4,5,6,7,7a-Hexahydro-4,7-methano-1H-inden-6-yl)oxy]ethyl acrylate 65983-31-5	LD50	> 5.000 mg/kg	rabbit	
2-Hydroxy-2-methylpropiophenone 7473-98-5	LD50	6.929 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Isobornyl acrylate 5888-33-5	LD50	> 3.000 mg/kg	rabbit	other guideline:
1,6-Hexanediol diacrylate 13048-33-4	LD50	3.650 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
2-Hydroxy-2-methylpropiophenone 7473-98-5	not irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Isobornyl acrylate 5888-33-5	irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1,6-Hexanediol diacrylate 13048-33-4	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
2-Hydroxy-2-methylpropiophenone 7473-98-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
1,6-Hexanediol diacrylate 13048-33-4	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
2-Hydroxy-2-methylpropiophenone 7473-98-5	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Isobornyl acrylate 5888-33-5	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
1,6-Hexanediol diacrylate 13048-33-4	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
2-Hydroxy-2-methylpropiophenone 7473-98-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-Hydroxy-2-methylpropiophenone 7473-98-5	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2-Hydroxy-2-methylpropiophenone 7473-98-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isobornyl acrylate 5888-33-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Isobornyl acrylate 5888-33-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Isobornyl acrylate 5888-33-5	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
1,6-Hexanediol diacrylate 13048-33-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1,6-Hexanediol diacrylate 13048-33-4	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1,6-Hexanediol diacrylate 13048-33-4	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Isobornyl acrylate 5888-33-5	NOAEL P 100 mg/kg NOAEL F1 100 mg/kg		oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
1,6-Hexanediol diacrylate 13048-33-4	NOAEL P 250 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
2-Hydroxy-2- methylpropiophenone 7473-98-5	NOAEL 50 mg/kg	oral: gavage	92-93 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Isobornyl acrylate 5888-33-5	NOAEL 100 mg/kg	oral: gavage	once daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
1,6-Hexanediol diacrylate 13048-33-4	NOAEL 250 mg/kg	oral: gavage	28 - 52 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2-[(3a,4,5,6,7,7a-Hexahydro-4,7-methano-1H-inden-6-yl)oxy]ethyl acrylate 65983-31-5	LC50	9 mg/l	96 h	Lepomis macrochirus	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-Hydroxy-2-methylpropiophenone 7473-98-5	LC50	160 mg/l	48 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Isobornyl acrylate 5888-33-5	LC50	0,704 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,6-Hexanediol diacrylate 13048-33-4	LC50	0,38 mg/l	96 h	Oryzias latipes	OECD Guideline 203 (Fish, Acute Toxicity Test)
1,6-Hexanediol diacrylate 13048-33-4	NOEC	0,072 mg/l	39 d	Oryzias latipes	OECD Guideline 210 (fish early lite stage toxicity test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2-Hydroxy-2-methylpropiophenone 7473-98-5	EC50	> 119 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Isobornyl acrylate 5888-33-5	EC50	1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1,6-Hexanediol diacrylate 13048-33-4	EC50	2,7 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Isobornyl acrylate 5888-33-5	NOEC	0,092 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
1,6-Hexanediol diacrylate 13048-33-4	NOEC	0,14 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2-Hydroxy-2-methylpropiophenone 7473-98-5	EC50	1,95 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-Hydroxy-2-methylpropiophenone 7473-98-5	NOEC	0,194 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isobornyl acrylate 5888-33-5	NOEC	0,405 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Isobornyl acrylate 5888-33-5	EC50	1,98 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,6-Hexanediol diacrylate 13048-33-4	EC50	2,33 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,6-Hexanediol diacrylate 13048-33-4	NOEC	0,9 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2-Hydroxy-2-methylpropiophenone 7473-98-5	EC 50	3 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
1,6-Hexanediol diacrylate 13048-33-4	EC20	60 mg/l	30 min	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The product is not biodegradable.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
2-[(3a,4,5,6,7,7a-Hexahydro-4,7-methano-1H-inden-6-yl)oxy]ethyl acrylate 65983-31-5		aerobic	0 %	30 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
2-Hydroxy-2-methylpropiophenone 7473-98-5	readily biodegradable	aerobic	90 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Isobornyl acrylate 5888-33-5	not readily biodegradable.	aerobic	57 %	28 d	OECD Guideline 310 (Ready Biodegradability CO2 in Sealed Vessels (Headspace Test))
1,6-Hexanediol diacrylate 13048-33-4	readily biodegradable	aerobic	69 %	28 d	OECD Guideline 310 (Ready Biodegradability CO2 in Sealed Vessels (Headspace Test))
1,6-Hexanediol diacrylate 13048-33-4	inherently biodegradable	aerobic	> 70 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)

12.3. Bioaccumulative potential

No data available.

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Isobornyl acrylate 5888-33-5	37	56 h	24 °C	Danio rerio	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

12.4. Mobility in soil

Cured adhesives are immobile.

Hazardous substances CAS-No.	LogPow	Temperature	Method
2-Hydroxy-2-methylpropiophenone 7473-98-5	1,62	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Isobornyl acrylate 5888-33-5	4,52		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
1,6-Hexanediol diacrylate 13048-33-4	2,81	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
2-Hydroxy-2-methylpropiophenone 7473-98-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Isobornyl acrylate 5888-33-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
1,6-Hexanediol diacrylate 13048-33-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Disposal of uncleaned packages:

Packaging that cannot be cleaned are to be disposed of in the same manner as the product.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information
--

14.1. UN number

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dicyclopentyloxyethyl acrylate)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dicyclopentyloxyethyl acrylate)
ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dicyclopentyloxyethyl acrylate)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dicyclopentyloxyethyl acrylate)
IATA	Environmentally hazardous substance, liquid, n.o.s. (Dicyclopentyloxyethyl acrylate)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	Marine pollutant
IATA	not applicable

14.6. Special precautions for user

ADR	not applicable Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), 197 (IATA), 969 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC content < 3 %
(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.